Abstract

The present invention relates to a bearing of a spindle motor for a hard disk drive which includes an aero dynamic pressure bearing which is fixedly installed in a space formed by a base and hub, a fluid dynamic pressure bearing which rotatably pivots the center of a in a radical direction and a thrust direction, and an air groove formed in such a manner that a certain space is formed between the hub and the aero dynamic pressure bearing after the hub is driven, wherein the aero dynamic pressure bearing and the fluid dynamic pressure bearing are directed to forming an upper side plane of which an upper side is extended in an outer radical direction like a spinning top for thereby implementing a conical shape in which a width of a lower side is decreased in a vertical direction.

5

10

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

f

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 11 December 2003 (11.12.2003)

PCT

(10) International Publication Number WO 03/102945 A1

(51) International Patent Classification7:

- (21) International Application Number: PCT/KR03/01098
- (22) International Filing Date:

Korean

G11B 19/20

(25) Filing Language: (26) Publication Language:

10-2002-0031221

English

(30) Priority Data:

4 June 2002 (04.06.2002)


4 June 2003 (04.06.2003)

- (71) Applicant (for all designated States except US): G & W TECHNOLOGIES CORP. [KR/KR]; 2nd Fls., 381-2 Munhak-dong, Nam-gu, Incheon 402-070 (KR).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): KIM, Sang-Uk [KR/KR]; Hongjewon Hyundai Apartment 103-1803, Hongje 4(sa)-dong, Seodaemun-gu, Seoul 120-094 (KR).

- (74) Agent: CHUNG, Yeon-Yong; #1203 Hyundai Topics Bldg., 44-3 Bangi-dong, Songpa-gu, Seoul 138-050 (KR).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: HYBRID DYNAMIC PRESSURE BEARING OF SPINDLE MOTOR



(57) Abstract: The present invention relates to a bearing of a spindle motor for a hard disk drive which includes an aero dynamic pressure bearing which is fixedly installed in a space formed by a base and hub, a fluid dynamic pressure bearing which rotatably pivots the center of a hub in a radial direction and a thrust direction, and an air groove formed in such a manner that a certain space is formed between the hub and the aero dynamic pressure bearing after the hub is driven, wherein the aero dynamic pressure bearing and the fluid dynamic pressure bearing are directed to forming an upper side plane of which an upper side is extended in an outer radial direction like a spinning top for thereby implementing a conical shape in which a width of a lower side is decreased in a vertical direction.



WO 03/102945 A1